

15522

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p>A root hole, bears S. 70° E., 85½ lks. dist., with a down fir alongside, 20 ins. diam., with scribe marks ¼ S12 CS BT visible on bark blaze.</p> <p>and a bearing tree mkd. by Byron</p> <p>A fir, 9 ins. diam., bears S. 34° W., 32½ lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 5 W ¼ $\frac{S 1}{S 12}$ 1969</p> <hr/> <p>N. 89° 29' E., beginning new measurement.</p> <p>Ascend 30 ft. along N. slope.</p>
7.00	Top of ascent, slopes N.; desc. 160 ft. over broken N. slope.
17.70	Slope changes to NE. slope.
18.84	From this point, a local corner, established by A. R. Evans, Deputy County Surveyor, in 1951, bears South, 0.024 chs. dist., monumented with an iron pipe, ½ in. diam., firmly set, projecting 6 ins. above ground, from which a bearing tree mkd. by Evans.
	<p>A fir, 8 ins. diam., bears S. 25° W., 14 lks. dist., with healed double blaze.</p>
21.90	Ravine, drains N. 10° E.; asc. 120 ft. over broken N. slope.
29.00	Slope changes to NW. slope.
32.50	Spur, slopes N. 25° E.; desc. 155 ft. over E. slope.
36.34	The closing cor. of secs. 1 and 12, on the W. bdy. of sec. 7, T. 30 S., R. 4 W.
	<p>From this point, the cor. of secs. 6 and 7 only, T. 30 S., R. 4 W., bears N. 0° 26' E., 2.91 chs. dist.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, oak, cedar, madrone, maple, dogwood, yew, and cascara; undergrowth, fern, salal, poison oak, vine maple, Oregon grape, blackberry, thimbleberry, hazel, and reproduction.</p>
	<p>The point for the ¼ sec. cor. of sec. 1 only, T. 30 S., R. 5 W., is at proportionate distance on the E. bdy. of sec. 1.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>