

15523

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">T 30 S $\frac{1}{2}$ S 1 R 5 W 1969</p> <p>from which</p> <p>A fir, 10 ins. diam., bears S. $29\frac{1}{2}^{\circ}$ W., $64\frac{1}{2}$ lks. dist., mkd. $\frac{1}{2}$ S1 BT.</p> <p>A fir, 26 ins. diam., bears N. $\frac{1}{2}^{\circ}$ W., $69\frac{1}{2}$ lks. dist., mkd. $\frac{1}{2}$ S1 BT.</p> <p>From this point, the $\frac{1}{2}$ sec. cor. of sec. 6 only, T. 30 S., R. 4 W., bears N. $0^{\circ} 41'$ E., 2.76 chs. dist., hereinbefore described.</p>
	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>N. $1^{\circ} 15'$ E., bet. secs. 1 and 2.</p> <p>Descend 35 ft. along W. slope, through old burn with scattered timber and moderate undergrowth.</p>
0.90	Gravelled road, 10 lks. wide, bears NE. and SW.
3.25	Creek, 3 lks. wide, course S. 35° W.; asc. 375 ft. over S. slope.
17.80	Spur ridge, slopes SW.; asc. 20 ft. along W. slope.
19.65	Point for the S $1/16$ sec. cor. of secs. 1 and 2.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>S $1/16$ S 2 S 1 1969</p>
	<p>from which</p> <p>An oak, 18 ins. diam., bears S. 62° E., 69 lks. dist., mkd. S $1/16$ S1 BT.</p> <p>An oak, 18 ins. diam., bears N. 55° W., 43 lks. dist., mkd. S $1/16$ S2 BT.</p> <p>Descend 105 ft. over NW. slope.</p>
37.85	Creek, 1 lk. wide, course S. 55° W., also enter field, edge bears N. 55° E. and S. 55° W.; asc. 50 ft. over SW. slope.
39.30	The $\frac{1}{2}$ sec. cor. of secs. 1 and 2, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	<p>COUNTY SURVEYORS OFFICE T 30 S S 2 S 1 R 5 W 1963</p>
	from which the remains of the original bearing trees