

15524

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p>An oak stump, 31 ins. diam., bears S. $12\frac{1}{2}^{\circ}$ E., 195 lks. dist., with a down and burned log alongside, 31 ins. diam., no marks visible.</p> <p>An oak, 18 ins. diam., bears S. $12\frac{1}{2}^{\circ}$ W., 215 lks. dist., with healed blaze. (Record, 220 lks.)</p> <p>and bearing trees mkd. by Byron</p> <p>A fir, 17 ins. diam., bears S. 27° E., 132 lks. dist., with healed blaze.</p> <p>A fir, 13 ins. diam., bears S. $1\frac{1}{2}^{\circ}$ E., $153\frac{1}{2}$ lks. dist., with healed double blaze.</p> <hr/> <p>N. $0^{\circ} 27'$ W., beginning new measurement.</p> <p>Ascend 370 ft. over SW. slope.</p>
16.00	<p>Ridge, bears N. 35° E. and S. 70° W., with spur ridge extending S. 50° E.; desc. 50 ft. along W. slope.</p>
20.16	<p>Point for the N 1/16 sec. cor. of secs. 1 and 2.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 2 S 1 1969</p> <p>from which</p> <p>A fir, 20 ins. diam., bears S. $47\frac{1}{2}^{\circ}$ E., 196 lks. dist., mkd. N 1/16 S1 BT.</p> <p>An oak, 11 ins. diam., bears S. 4° W., 112 lks. dist., mkd. N 1/16 S2 BT.</p> <p>Descend 235 ft. along broken W. slope, through new logged area.</p>
41.00	<p>Spur, slopes W.; desc. 60 ft. over NW. slope.</p>
43.05	<p>The closing cor. of secs. 1 and 2, on the S. bdy. of sec. 36, T. 29 S., R. 5 W.</p> <p>From this point, the cor. of secs. 35 and 36 only, T. 29 S., R. 5 W., bears S. $89^{\circ} 38'$ W., 5.24 chs. dist.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, oak, cedar, madrone, maple, dogwood, yew, and cascara; undergrowth, fern, salal, poison oak, vine maple, Oregon grape, blackberry, thimbleberry, hazel, and reproduction.</p>
	<p>The point for the $\frac{1}{4}$ sec. cor. of sec. 1 only T. 30 S., R. 5 W., is at proportionate distance on the N. bdy. of sec. 1.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>