

15526

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
0.20	Board gate in fence, extends E. and W.
3.05	Ravine, drains S. 65° E.; asc. 140 ft. over S. slope.
4.40	Dirt road, 20 lks. wide, bears N. 40° E. and S. 40° W.
16.70	Enter timber, edge bears E. and W.
19.89	Point for the S 1/16 sec. cor. of secs. 14 and 15. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. S 1/16 S 15 S 14 1969 from which A fir, 7 ins. diam., bears N. 31½° E., 19½ lks. dist., mkd. S 1/16 S14 BT. A fir, 8 ins. diam., bears N. 62½° W., 34 lks. dist., mkd. S 1/16 S15 BT. Ascend 200 ft. over S. slope.
20.30	Wire fence, extends E. and W.
22.70	Gravelled road, 20 lks. wide, bears E. and W.
27.40	Spur, slopes S. 50° E.; asc. 130 ft. along E. slope.
39.78	Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 30 S R 5 W ¼ S 15 S 14 1969 from which A cedar, 12 ins. diam., bears N. 51½° E., 39 lks. dist., mkd. ¼ S14 BT. A fir, 13 ins. diam., bears S. 60½° W., 32 lks. dist., mkd. ¼ S15 BT. Ascend 90 ft. along E. slope.
47.20	Spur, slopes N. 80° E.; desc. 110 ft. over NE. slope.
55.90	Ravine, drains S. 65° E.; asc. 85 ft. over SE. slope.
61.20	Spur, slopes S. 70° E.; desc. 5 ft. along E. slope.
67.90	Bottom of descent, slopes SE.; asc. 155 ft. over SE. slope.
79.56	The cor. of secs. 10, 11, 14, and 15, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1958, from original evidence no longer in existence, monumented with an iron pipe, ¾ in. diam., firmly