

15527

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS					
	<p>set, projecting 6 ins. above ground, from which the remains of bearing trees mkd. by Markham:</p> <p>A fir, 8 ins. diam., bears N. 27½° E., 69 lks. dist., with scribe marks S11 B visible on partially healed double blaze.</p> <p>A root hole, bears N. 87½° E., 62 lks. dist., with a down fir alongside, 17 ins. diam., with scribe marks S14 BT visible on partially healed blaze.</p> <p>A fir, 16 ins. diam., bears S. 71° W., 50 lks. dist., with healed double blaze.</p> <p>A fir, 23 ins. diam., bears N. 21½° W., 27 lks. dist., with scribe marks S10 BT visible on bark blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 30 S R 5 W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 10</td> <td style="padding: 0 5px;">S 11</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> </table> <p>1969</p> </div> <p>from which a new bearing tree</p> <p>A fir, 20 ins. diam., bears S. 34½° E., 108 lks. dist., mkd. T30S R5W S14 BT.</p> <p>Land, mountainous. Soil, rocky clay and loam. Timber, fir, pine, oak, cedar, madrone, maple, dogwood, yew, and cascara; undergrowth, fern, salal, poison oak, arrowwood, vine maple, Oregon grape, blackberry, hazel, thimbleberry, and reproduction.</p>	S 10	S 11	S 15	S 14
S 10	S 11				
S 15	S 14				
	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>N. 87° 39' W., bet. secs. 11 and 14.</p> <p>Ascend 175 ft. over broken NE. slope, through old logged area with moderate undergrowth.</p>				
15.80	<p>Spur, slopes S. 30° E.; also dirt road, 15 lks. wide, bears N. 30° W. and S. 30° E.; desc. 55 ft. over W. slope.</p>				
21.10	<p>Ravine, drains S. 15° W.; asc. 50 ft. over E. slope.</p>				
25.00	<p>Spur, slopes S. 25° W.; desc. 75 ft. over SW. slope.</p>				
31.30	<p>Wire fence, extends N. 70° W. and S. 70° E., also enter open field, edge bears same as fence.</p>				
32.20	<p>Creek, 1 lk. wide, course S. 20° E.; asc. 105 ft. over SE. slope.</p>				
38.16	<p>The ¼ sec. cor. of secs. 11 and 14, re-established by John H. Markham, Jr., Registered Engineer No. 2880, in 1958, monumented with an iron pipe, 1 in. diam., firmly set flush with the ground, and subsequently perpetuated</p>				