

15528

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p>and recorded by James W. Byron, Deputy County Surveyor, in 1963, with an iron post, 1 in. diam., firmly set along side, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 30 S $\frac{1}{2}$ $\frac{S 11}{S 14}$ R 5 W 1963</p> <p>from which bearing trees mkd. by Markham</p> <p>A black oak, 10 ins. diam., bears N. $8\frac{1}{2}^{\circ}$ E., 105 lks. dist., with healed double blaze.</p> <p>A white oak, 8 ins. diam., bears N. $27\frac{1}{2}^{\circ}$ E., $93\frac{1}{2}$ lks. dist., with healed double blaze.</p> <p>A madrone, 25 ins. diam., bears N. $51\frac{3}{4}^{\circ}$ W., 109 lks. dist., with scribe marks BT visible on partially healed double blaze.</p> <p>No new suitable tree available within limits in sec. 14.</p> <p style="text-align: center;">—————</p> <p>N. $87^{\circ} 46'$ W., beginning new measurement.</p> <p>Ascend 25 ft. over SE. slope.</p> <p>2.00 Spur, slopes S.; desc. 80 ft. over W. slope.</p> <p>6.65 Ravine, drains S.; asc. 60 ft. over SE. slope.</p> <p>13.50 Top of ascent slopes S.; desc. 60 ft. over SW. slope.</p> <p>19.55 Creek, 2 lks. wide, course S.; asc. 125 ft. over SE. slope.</p> <p>28.00 Spur, slopes S. 20° E.; desc. 20 ft. over SW. slope.</p> <p>29.10 Ravine, drains S. 20° E.; asc. 135 ft. over SE. slope.</p> <p>33.80 Spur, slopes S. 10° W.; desc. 110 ft. over NE. slope.</p> <p>37.90 Ravine, drains S.; asc. 10 ft. over SE. slope.</p> <p>38.14 The cor. of secs. 10, 11, 14, and 15.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, pine, oak, cedar, madrone, maple, dogwood, yew, and cascara; undergrowth, fern, salal, poison oak, arrowwood, vine maple, Oregon grape, blackberry, hazel, thimbleberry, and reproduction.</p>
	<p>N. $0^{\circ} 50'$ W., bet. secs. 10 and 11.</p> <p>Ascend 315 ft. over SE. slope, through medium timber and moderate undergrowth.</p> <p>10.30 Ridge, bears N. 55° E. and S. 55° W., also enter logged area, edge bears same; desc. 40 ft. over NW. slope.</p> <p>13.00 Spur, slopes N. 55° W.; desc. 140 ft. over broken N. slope.</p>