

15529

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

<p>CHAINS 18.90</p>	<p>Point for the S 1/16 sec. cor. of secs. 10 and 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p>FOOK PER JOHNSTONE 11/86 M103-1</p> <p style="margin-left: 150px;">S 1/16 S 10 S 11 1969</p> <p>from which</p> <p style="margin-left: 40px;">A fir, 30 ins. diam., bears N. 47¾° E., 75 lks. dist., mkd. S 1/16 S11 BT.</p> <p style="margin-left: 40px;">A fir, 27 ins. diam., bears N. 6½° W., 93 lks. dist., mkd. S 1/16 S10 BT.</p> <p>Descend 300 ft. over broken NE. slope.</p>
<p>31.40</p>	<p>Creek, 2 lks. wide, course N. 25° W.; desc. 35 ft. along W. slope.</p>
<p>35.10</p>	<p>Spur, slopes N. 40° W.; desc. 105 ft. over NW. slope.</p>
<p>37.30</p>	<p>Morgan Creek, 8 lks. wide, course E.; asc. 5 ft. over S. slope.</p>
<p>37.80</p>	<p>The ¼ sec. cor. of secs. 10 and 11, perpetuated and recorded by John H. Markham, Registered Engineer No. 2880, in 1958, monumented with the remains of the original corner tree, a dead topped maple, 16 ins. diam., with scribe mark 4 visible on partially healed blaze on W., and ¼ S visible on E. faces, with an iron pipe, ¾ in. diam., firmly set alongside, projecting 6 ins. above ground, from which the remains of the original bearing trees:</p> <p style="margin-left: 40px;">FOOK PER JOHNSTONE 11/86 M103-1</p> <p style="margin-left: 40px;">A maple root crown, size indeterminate, bears N. 61° E., 7 lks. dist., no marks visible.</p> <p style="margin-left: 40px;">A maple, 16 ins. diam., bears N. 88° W., 63 lks. dist., no marks visible.</p> <p>and the remains of bearing trees mkd. by Markham</p> <p style="margin-left: 40px;">A yew, 13 ins. diam., bears S. 47½° W., 105 lks. dist., with scribe marks ¼ S10 BT visible on partially healed double blaze.</p> <p style="margin-left: 40px;">A root hole, bears N. 54° W., 63 lks. dist., with a down fir alongside, 7 ins. diam., with scribe marks ¼ S10 BT visible on open decayed double blaze.</p> <p style="margin-left: 40px;">A maple, 15 ins. diam., bears N. 31¾° W., 95 lks. dist., with scribe marks ¼ S10 BT visible on partially healed double blaze.</p> <p>and which a reference monument</p> <p style="margin-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° E., 10 lks. dist., with brass cap mkd. T30S R5W ¼ S11 RM 1969 and an arrow pointing to the corner.</p>