

15530

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
6.80	<p>N. 1° 04' W., beginning new measurement.</p> <p>Ascend 340 ft. over S. slope.</p>
11.70	<p>Enter timber, edge bears E. and W.</p> <p>Spur, slopes E., also enter old logged area with dense undergrowth, edge bears E. and W.; desc. 265 ft. over N. slope.</p>
18.83	<p>Point for the N 1/16 sec. cor. of secs. 10 and 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 10 S 11 1969</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 54° E., 47 lks. dist., mkd. N 1/16 S11 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 81° W., 107 lks. dist., mkd. N 1/16 S10 BT.</p>
20.90	<p>Descend 60 ft. over N. slope.</p> <p>Creek, 4 lks. wide, course S. 80° E.; asc. 520 ft. over S. slope.</p>
22.40	<p>Dirt road, 15 lks. wide, bears E. and W.</p>
37.66	<p>The cor. of secs. 2, 3, 10, and 11, perpetuated and recorded by Burton W. Holt, RLS No. 418, in 1958, monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above ground, with a washed boulder alongside, 14 x 6 x 5 ins., firmly set 8 ins. in the ground, mkd. with S2 on NE., S11 on SE., S10 on SW., and S3 on NW. faces, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A black oak, 25 ins. diam., bears N. 50¼° E., 47 lks. dist., no marks visible on opened decayed blaze. (Record, N. 49¾° E., 44 lks.)</p> <p style="padding-left: 40px;">A pine, 28 ins. diam., bears S. 39¾° W., 123 lks. dist., with scribe marks 10 visible on opened blaze. (Record, S. 38¾° W., 125 lks.)</p> <p style="padding-left: 40px;">A black oak, 30 ins. diam., bears N. 60¾° W., 108 lks. dist., with scribe marks S2 visible on opened blaze. (Record, N. 61¼° W., 111 lks.)</p> <p>and bearing trees mkd. by Holt</p> <p style="padding-left: 40px;">A madrone, 8 ins. diam., bears N. 21¼° E., 49 lks. dist., with scribe marks S2 X BT visible on partially healed double blaze.</p> <p style="padding-left: 40px;">A madrone, 5 ins. diam., bears N. 54¾° E., 39½ lks. dist., with scribe marks S2 BT visible on partially healed double blaze.</p> <p style="padding-left: 40px;">A madrone, 8 ins. diam., bears S. 21¾° E., 20 lks. dist., with scribe marks S11 T30S BT visible on partially healed double blaze.</p>