

15531

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS					
	<p>A madrone, 12 ins. diam., bears S. 79½° W., 99 lks. dist., with scribe marks S10 BT R5W visible on partially healed double blaze.</p> <p>A madrone, 9 ins. diam., bears N. 10¼° W., 41 lks. dist., with scribe marks S3 BT visible on partially healed double blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 30 S R 5 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 10</td> <td style="padding: 0 5px;">S 11</td> </tr> </table> <p>1969</p> </div> <p>Deposit washed boulder alongside iron post.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, pine, oak, madrone, maple, dogwood, cedar, yew, and cascara; undergrowth, fern, salal, poison oak, arrowwood, vine maple, Oregon grape, blackberry, hazel, thimbleberry, and reproduction.</p>	S 3	S 2	S 10	S 11
S 3	S 2				
S 10	S 11				
	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>N. 89° 36' W., bet. secs. 2 and 11.</p> <p>Descend 65 ft. over NW. slope, through old burn with scattered timber and moderate undergrowth.</p>				
1.10	Gravelled road, 15 lks. wide, bears NE. and SW., curving S.				
3.00	Creek, 3 lks. wide, course S. 30° W.; asc. 180 ft. over SE. slope.				
10.15	Spur, slopes S. 30° W.; desc. 310 ft. over NW. slope.				
20.50	Creek, 5 lks. wide, course S. 10° W.; asc. 440 ft. over E. slope.				
20.85	Morgan Creek Road, gravelled, 15 lks. wide, bears N. 10° E. and S. 10° W.; also enter timber, edge bears same.				
27.60	Slope changes to NE. slope.				
35.60	Spur ridge, bears N. 15° W. and S. 15° E.; desc. 20 ft. over SW. slope.				
37.99	<p>The ¼ sec. cor. of secs. 2 and 11, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1958, from original evidence no longer in existence, and subsequently perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above ground, from which the remains of bearing trees mkd. by Markham:</p> <p>A fir stump, 10 ins. diam., bears N. 21° W., 92½ lks. dist., with scribe marks ¼ S2 BT visible on partially healed double blaze.</p>				