

15532

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

A fir snag, 12 ins. diam., bears N. $80\frac{1}{2}^\circ$ W., 71 lks. dist., with scribe marks $\frac{1}{4}$ S2 BT visible on partially healed double blaze.

A cedar, 18 ins. diam., bears S. $78\frac{1}{2}^\circ$ W., $80\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S11 T30S R5W BT visible on partially healed double blaze.

and a bearing tree mkd. by Byron

A fir, 17 ins. diam., bears N. 82° W., $91\frac{1}{2}$ lks. dist., with illegible scribe marks visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.

T 30 S R 5 W
 $\frac{1}{4}$ $\frac{S 2}{S 11}$
1969

N. $89^\circ 26'$ W., beginning new measurement.

Descend 135 ft. over SW. slope, through medium timber and moderate undergrowth.

11.00 Ravine, drains S. 35° W.; asc. 10 ft. over SE. slope.

13.20 Spur, slopes S. 20° W.; desc. 140 ft. over SW. slope.

19.55 The W $1/16$ sec. cor. of secs. 2 and 11, established by Burton W. Holt, RLS No. 418, in 1958, monumented with an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, projecting 15 ins. above ground, from which bearing trees mkd. by Holt:

A white oak, 12 ins. diam., bears N. 81° E., 108 lks. dist., with healed double blaze.

A fir, 11 ins. diam., bears S. 69° E., 84 lks. dist., with healed double blaze.

A madrone, 15 ins. diam., bears S. 60° E., 85 lks. dist., with scribe marks $1/16$ S S11 BT visible on bark.

A fir, 13 ins. diam., bears S. 25° E., $18\frac{1}{2}$ lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.

W $1/16$ $\frac{S 2}{S 11}$
1969

N. $89^\circ 10'$ W., beginning new measurement.