

15533

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	Descend 10 ft. over SW. slope.
0.20	Creek, 2 lks. wide, course S.; asc. 425 ft. over SE. slope.
1.15	Enter open field, edge bears N. and S.
3.20	Dirt road, 10 lks. wide, bears N. 20° E. and S. 20° W.
12.40	Enter timber, edge bears N. and S.
19.63	The cor. of secs. 2, 3, 10, and 11.
	Land, mountainous. Soil, rocky clay. Timber, fir, pine, oak, cedar, maple, madrone, dogwood, yew, and cascara; undergrowth, fern, salal, poison oak, arrowwood, vine maple, Oregon grape, blackberry, hazel, thimbleberry, and reproduction.
	N. 0° 43' W., bet. secs. 2 and 3.
	Ascend 90 ft. over SE. slope, through medium timber and moderate undergrowth.
9.85	Ridge, bears N. 30° E. and S. 30° W.; desc. 35 ft. along W. slope.
19.88	Point for the S 1/16 sec. cor. of secs. 2 and 3.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	S 1/16 S 3 S 2 1969
	from which
	A fir, 13 ins. diam., bears N. 19° E., 35 lks. dist., mkd. S 1/16 S2 BT.
	A fir, 10 ins. diam., bears S. 5° W., 15½ lks. dist., mkd. S 1/16 S3 BT.
	Descend slightly along W. slope.
20.10	Bottom of descent, slopes W.; asc. 50 ft. along W. slope.
29.40	Spur, slopes N. 30° E.; desc. 280 ft. over NW. slope.
39.76	The ¼ sec. cor. of secs. 2 and 3, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1951, and subsequently perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground, from which the remains of the original bearing trees:
	A fir, 27 ins. diam., bears N. 42½° W., 20 lks. dist., with healed blaze and scribe marks ¼ S3 visible on bark blaze. This tree was rescribed by Markham.
	and the remains of a bearing tree mkd. by Markham