

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

15536

CHAINS	
	From this point, the E 1/16 sec. cor. of sec. 35 only, T. 29 S., R. 5 W., bears S. 89° 37' W., 5.30 chs. dist., hereinbefore described.
	From the cor. of secs. 14, 15, 22, and 23. S. 89° 51' W., bet. secs. 15 and 22. Ascend 25 ft. over gentle E. slope, along gravelled road, 15 lks. wide.
0.25	Cattle guard in fence, bears N. and S.
5.70	Spur, slopes S. 30° E.; desc. 50 ft. over SW. slope.
9.70	Leave gravelled road, 15 lks. wide, bears S. and E., also enter timber and moderate undergrowth, edge bears N. and S.
12.80	Dry bed of creek, 2 lks. wide, drains SE.; asc. 50 ft. over SE. slope.
22.70	Wire fence, bears N. and S.
25.10	Enter open field, edge bears N. and S.
27.30	Top of ascent, slopes S.; desc. 30 ft. over gentle SW. slope.
37.35	Wire fence, bears N. and S.
39.50	Wire fence, bears N. 10° E. and S. 10° W.
40.12	The 1/4 sec. cor. of secs. 15 and 22, determined at record bearing and distance from the remains of the original bearing trees: An oak snag, 14 ins. diam., bears S. 45° E., 12 lks. dist., with scribe marks BT visible in negative on overgrowth. At the corner point Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 30 S R 5 W 1/4 S 15 S 22 1967 from which new bearing trees A fir, 15 ins. diam., bears N. 45 1/2° E., 13 lks. dist., mkd. 1/4 S15 BT. An oak, 28 ins. diam., bears S. 81 1/2° W., 17 lks. dist., mkd. 1/4 S22 BT. N. 88° 24' W., beginning new measurement. Descend 5 ft. over gentle SW. slope, through scattered timber and moderate undergrowth.
1.60	Dirt road, 15 lks. wide, bears NE. and NW., in curve.