

Dependent Resurvey, Portion of Subdivisional Lines, **15538**
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p>A white oak, 5 ins. diam., bears N. 85° W., 17 lks. dist., with scribe marks S16 CS BT visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 5 W S 16 S 15 S 21 S 22 1967</p> <p>Land, nearly level. Soil, rocky clay and loam. Timber, fir, pine, oak, cedar, maple, madrone, dogwood, yew, and cascara; undergrowth, fern, salal, poison oak, arrowwood, vine maple, Oregon grape, blackberry, hazel, thimbleberry, and reproduction.</p>
	<p>N. 1° 14' E., bet. secs. 15 and 16.</p> <p>Ascend 80 ft. over S. slope, through medium timber and dense undergrowth.</p>
6.10	Dirt road, 10 lks. wide, bears N. 50° E. and S. 50° W.
6.70	Spur ridge, bears N. 55° E. and S.; desc. 80 ft. over NW. slope.
11.60	Bottom of descent, slopes W.; asc. 15 ft. along W. slope.
19.67	Point for the S 1/16 sec. cor. of secs. 15 and 16.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 16 S 15 1969</p> <p>from which</p> <p>A fir, 11 ins. diam., bears N. 58° E., 85 lks. dist., mkd. S 1/16 S15 BT.</p> <p>A fir, 13 ins. diam., bears S. 58° W., 2½ lks. dist., mkd. S 1/16 S16 BT.</p> <p>Ascend 205 ft. over S. slope.</p>
28.70	Spur ridge, bears N. 15° W. and S. 15° E.; desc. 120 ft. over NE. slope.
35.80	Ravine, drains N. 75° E.; asc. 20 ft. over SE. slope.
36.90	Spur, slopes E.; desc. 60 ft. over NE. slope.
39.34	Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>