

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	Ascend 115 ft. over SE. slope, through medium timber and moderate undergrowth.
3.50	Spur, slopes S. 30° E.; desc. 20 ft. along S. slope.
5.80	Ravine, drains S. 15° E.; asc. 275 ft. over SE. slope.
12.80	Dirt road, 15 lks. wide, bears N. 5° W. and SW., in curve, also enter logged area, edge bears same.
19.97	Point for the E 1/16 sec. cor. of secs. 10 and 15.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: right;">FDOX PER JOHNSTONE 11/36 m103-1</p> <p style="text-align: center;">E 1/16 $\frac{S 10}{S 15}$ 1969</p>
	from which
	A fir, 20 ins. diam., bears N. 69° W., 93 lks. dist., mkd. E 1/16 S10 BT.
	A fir, 18 ins. diam., bears S. 21° W., 61 lks. dist., mkd. E 1/16 S15 BT.
	Ascend 15 ft. over E. slope, through medium timber and undergrowth.
24.30	Ridge, bears NE. and S. 70° W.; desc. 145 ft. along broken N. slope.
36.40	Enter logged area, edge bears N. and S.
39.94	The ¼ sec. cor. of secs. 10 and 15, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1958, and subsequently perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, ¾ in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.
	<p style="text-align: center;">COUNTY SURVEYORS OFFICE T 30 S FDOX PER JOHNSTONE $\frac{S 10}{S 15}$ 11/36 m103-1 R 5 W 1963</p>
	from which the remains of bearing trees mkd. by Thiel
	A root hole, bears N. 45° W., 16 lks. dist., with a down pine alongside, 41 ins. diam., with scribe marks ¼ BT visible on opened blaze.
	and the remains of bearing trees mkd. by Markham
	A madrone, 35 ins. diam., bears N. 28° E., 51½ lks. dist., with scribe marks ¼ S10 BT visible on partially healed double blaze.
	A fir snag, 10 ins. diam., bears N. 59° E., 47 lks. dist., with scribe marks ¼ S10 BT visible on partially healed double blaze.
	A madrone stump, 20 ins. diam., bears S. 26° E., 76 lks. dist., with a down madrone alongside, 20 ins. diam., with scribe marks ¼ S15 BT visible on open double blaze.