

15541

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p>and a new bearing tree</p> <p>A fir, 45 ins. diam., bears S. 70$\frac{1}{4}$° E., 29$\frac{1}{2}$ lks. dist., mkd. $\frac{1}{2}$ S15 BT.</p> <p>Corner is located in bottom of descent, slopes N.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 11' W., beginning new measurement.</p> <p>Ascend 105 ft. along broken N. slope.</p>
10.30	Gravelled road, 20 lks. wide, bears N. 65° W. and S. 65° E., also enter timber, edge bears same.
11.50	Spur ridge, bears N. 65° W. and S. 65° E.; desc. 180 ft. over SW. slope.
19.86	<p>Point for the W 1/16 sec. cor. of secs. 10 and 15.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p>FD OK PER JOHNSTONE 11/86 m103-1 W 1/16 $\frac{S}{S}$ $\frac{10}{15}$ 1969</p> <p>from which</p> <p>A fir, 28 ins. diam., bears N. 28$\frac{1}{2}$° E., 31 lks. dist., mkd. W 1/16 S10 BT.</p> <p>A fir, 46 ins. diam., bears S. 42$\frac{1}{4}$° E., 36 lks. dist., mkd. W 1/16 S15 BT.</p> <p>Descend 65 ft. over SW. slope.</p>
21.80	Creek, 3 lks. wide, course S. 15° W.; asc. 80 ft. over SE. slope.
25.10	Spur, slopes S. 10° E.; desc. 10 ft. over SW. slope.
27.80	Ravine, drains S. 20° E.; asc. 50 ft. over SE. slope.
29.70	Spur, slopes S. 10° E.; desc. 45 ft. over broken SW. slope.
34.30	Ravine, drains S. 5° W.; asc. 160 ft. over SE. slope.
38.60	Spur, slopes S. 20° E.; desc. 10 ft. over SW. slope.
39.72	The cor. of secs. 9, 10, 15, and 16.
	<p>Land, mountainous. Soil, rocky clay. Timber, fir, pine, oak, cedar, maple, madrone, dogwood, yew, and cascara; undergrowth, fern, salal, poison oak, arrowwood, vine maple, Oregon grape, blackberry, hazel, thimbleberry, and reproduction.</p>
	<p>N. 0° 38' W., bet. secs. 9 and 10.</p> <p>Ascend 90 ft. over SW. slope, through medium timber and moderate undergrowth.</p>
3.10	Spur, slopes S. 10° E.; asc. 180 ft. over SE. slope.