

15543

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	A fir stump, 13 ins. diam., bears S. 45° W., 41 lks. dist., no marks visible.
	—————
	N. 0° 50' W., beginning new measurement.
	Descend 405 ft. over broken NW. slope, through logged area.
14.90	Ravine, drains N. 50° W.; asc. 20 ft. over SW. slope.
18.87	Point for the N 1/16 sec. cor. of secs. 9 and 10.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	N 1/16 S 9   S 10 1969
	from which
	A fir, 11 ins. diam., bears N. 50° E., 53½ lks. dist., mkd. N 1/16 S10 BT.
	A fir, 15 ins. diam., bears N. 45° W., 85 lks. dist., mkd. N 1/16 S9 BT.
	Ascend 20 ft. over SW. slope.
20.20	Spur, slopes N. 65° W.; desc. 275 ft. over NW. slope.
26.10	Creek, 2 lks. wide, course W.; asc. 315 ft. over SW. slope.
33.70	Spur, slopes S. 75° W.; desc. 70 ft. over NW. slope.
37.74	The cor. of secs. 3, 4, 9, and 10, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1959, from original evidence no longer in existence, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE S 4   S 3 S 9   S 10 T 30 S R 5 W 1959
	from which bearing trees mkd. by Byron
	A fir, 10 ins. diam., bears N. 61½° E., 12 lks. dist., with healed double blaze.
	A fir, 16 ins. diam., bears S. 57¾° E., 37 lks. dist., with healed double blaze.
	A fir, 20 ins. diam., bears S. 4¾° W., 22½ lks. dist., with healed double blaze.
	A fir, 16 ins. diam., bears N. 25½° W., 65½ lks. dist., with healed double blaze.
	Corner is located at a fence corner, wire fences extend N. and S. 75° W.