

15544

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p>Land, mountainous. Soil, rocky clay. Timber, fir, pine, cedar, oak, and madrone; undergrowth, hazel, arrowwood, poison oak, maple, and fern.</p>
	<p>From the cor. of secs. 2, 3, 10, and 11. N. 88° 47' W., bet. secs. 3 and 10. Ascend 25 ft. over SE. slope, through medium timber and moderate undergrowth.</p>
8.55	Spur, slopes S. 35° W.; desc. 345 ft. over W. slope.
17.77	Creek, 5 lks. wide, course S. 15° W.; asc. 85 ft. over E. slope.
19.82	Point for the E 1/16 sec. cor. of secs. 3 and 10. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> $E \frac{1}{16} \frac{S \ 3}{S \ 10}$ 1969 </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears N. 74° W., 15 lks. dist., mkd. E 1/16 S3 BT.</p> <p style="margin-left: 40px;">A cedar, 15 ins. diam., bears S. 21° W., 25½ lks. dist., mkd. E 1/16 S10 BT.</p> <p>Ascend 200 ft. over E. slope.</p>
26.00	Spur, slopes S. 10° E.; desc. 170 ft. over SW. slope.
38.40	Creek, 1 lk. wide, course SE., also corner of timber, edge bears N., S., E., and W.; asc. 15 ft. over E. slope, over logged area.
39.64	Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> $T \ 30 \ S \ R \ 5 \ W$ $\frac{1}{4} \frac{S \ 3}{S \ 10}$ 1969 </div> <p style="text-align: right; margin-right: 20px;"><i>FOOL PER JOHNSTONE</i> 11186 m103-1</p> <p>from which</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears N. 62° E., 161 lks. dist., mkd. ¼ S3 BT.</p> <p style="margin-left: 40px;">A maple, 20 ins. diam., bears N. 22° W., 175 lks. dist., mkd. ¼ S3 BT.</p> <p>Ascend 355 ft. over E. slope.</p>
52.15	Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.