

15549

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	T 30 S R 5 W $\frac{S 8 S 9}{S 17 S 16}$ 1969
	from which A pine, 12 ins. diam., bears N. 57° E., 186 lks. dist., mkd. T30S R5W S9 BT. A madrone, 13 ins. diam., bears S. 57½° E., 179 lks. dist., mkd. T30 S R 5W S16 BT. A pine, 17 ins. diam., bears S. 43½° W., 244 lks. dist., mkd. T30S R5W S17 BT. A fir, 13 ins. diam., bears N. 26° W., 148 lks. dist., mkd. T30S R5W S8 BT. Land, mountainous. Soil, rocky clay. Timber, fir, pine, madrone, and oak; undergrowth, poison oak, arrowwood, and hazel.
	From the cor. of secs. 9, 10, 15, and 16. S. 89° 12' W., bet. secs. 9 and 16. Descend 20 ft. over SW. slope, through light timber and medium undergrowth.
1.05 9.45 14.20 20.90 24.85 31.30 39.26 39.41	Ravine, drains S. 25° E.; asc. 200 ft. over SE. slope. Spur, slopes S. 20° W.; desc. 75 ft. over SW. slope. Draw, drains S.; asc. 50 ft. along S. slope. Ridge, bears N. and S.; desc. 155 ft. over NW. slope. Draw, drains S. 60° W.; desc. 35 ft. along S. slope. Draw, drains S. 40° W.; desc. 125 ft. along S. slope. Point for the ¼ sec. cor. of sec. 16 only, at proportionate dist., there is no remaining evidence of the original corner. No permanent monument established. Point for the ¼ sec. cor. of sec. 9 only, at proportionate distance and on the S. bdy. of sec. 9. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 30 S R 5 W $\frac{1}{4} S 9$ 1969
	from which A fir, 13 ins. diam., bears N. 58° E., 17 lks. dist., mkd. ¼ S9 BT. An oak, 10 ins. diam., bears N. 22½° W., 11 lks. dist., mkd. ¼ S9 BT. Descend 545 ft. over W. slope.