

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

15550

56.00	<p>CHAINS Draw, drains S. 20° W.; asc. 215 ft. over E. slope.</p>
59.11	<p>Point for the W 1/16 sec. cor. of sec. 9 only.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"><u>W 1/16 S 9</u> 1969</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 1° E., 25 lks. dist., mkd. W 1/16 S9 BT.</p>
	<p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 10½° W., 61 lks. dist., mkd. W 1/16 S9 BT.</p>
	<p>Ascend 70 ft. over E. slope.</p>
61.00	<p>Spur, slopes S. 20° E.; asc. 65 ft. along S. slope.</p>
67.10	<p>Spur, slopes S. 10° W.; desc. 90 ft. over W. slope.</p>
72.00	<p>Draw, drains S. 30° W.; asc. 25 ft. over SE. slope.</p>
78.25	<p>Spur, slopes S. 30° W.; desc. 5 ft. over SW. slope.</p>
78.52	<p>The cor. of secs. 8, 9, 16, and 17.</p>
	<p>Land, mountainous. Soil, rocky clay. Timber, fir, pine, madrone, maple, and oak; undergrowth, poison oak, hazel, arrowwood, and fern.</p>
	<p>N. 0° 14' E., bet. secs. 8 and 9.</p>
	<p>Ascend 200 ft. over broken SW. slope, through medium timber and dense undergrowth.</p>
16.55	<p>Ravine, drains S. 10° W.; asc. 290 ft. over S. slope.</p>
25.85	<p>Spur, slopes SW.; desc. 30 ft. along W. slope.</p>
31.20	<p>Spur, slopes N. 70° W.; desc. 95 ft. over N. slope.</p>
35.65	<p>Ravine, drains NW.; desc. 10 ft. over NW. slope.</p>
35.95	<p>Spur, slopes NW.; desc. 40 ft. over N. slope.</p>
38.50	<p>Point for the ¼ sec. cor. of secs. 8 and 9, re-established by the irregular boundary method, based on the 1896 Thiel survey.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 30 S R 5 W ¼ S 8 S 9 1969</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 62½° E., 213 lks. dist., mkd. ¼ S9 BT.</p>