

384 15553

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	COUNTY SURVEYORS OFFICE T 30 S R 5 W S 19   S 20 $\frac{1}{2}$ 1960
	from which a bearing tree mkd. by Stewart  A black oak, 25 ins. diam., bears N. $68\frac{1}{2}^{\circ}$ E., 70 lks. dist., no marks visible on opened blaze.  and the remains of a bearing tree mkd. by Frear  A root hole, bears N. $33^{\circ}$ E., $37\frac{1}{2}$ lks. dist., with a down pine alongside, 15 ins. diam., no marks visible.  and a bearing tree reported by Byron  A root hole, bears N. $62^{\circ}$ E., $42\frac{1}{2}$ lks. dist., with a down madrone alongside, 14 ins. diam., with scribe marks $\frac{1}{2}$ S20 CS BT visible on open double blaze.  and a bearing tree mkd. by Byron  A black oak, 13 ins. diam., bears N. $25\frac{1}{2}^{\circ}$ W., $57\frac{1}{2}$ lks. dist., with healed double blaze.  N. $2^{\circ} 17'$ W., bet. secs. 19 and 20.  Descend 20 ft. over NE. slope, through light timber and undergrowth.  12.00 Bottom of descent, slopes E.; asc. 55 ft. over SE. slope.  18.25 Gazley Road, asphalt surfaced, 35 lks. wide, bears N. $40^{\circ}$ E. and S. $40^{\circ}$ W.  20.04 Point for the N 1/16 sec. cor. of secs. 19 and 20.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">             N 1/16              S 19   S 20              1969           </div> from which  A fir, 12 ins. diam., bears S. $58^{\circ}$ E., $42\frac{1}{2}$ lks. dist., mkd. N 1/16 S20 BT.  A fir, 6 ins. diam., bears N. $81\frac{1}{2}^{\circ}$ W., 4 lks. dist., mkd. N 1/16 S19 BT.  Ascend 330 ft. over SE. slope.  21.70 Dirt road, 15 lks. wide, bears E. and W.  33.50 Same dirt road, 15 lks. wide, bears N. $55^{\circ}$ E. and S. $55^{\circ}$ W.; also ridge, bears same; desc. 145 ft. over NW. slope.  40.08 Point for the cor. of secs. 17, 18, 19, and 20, at proportionate distance; there is no remaining evidence of the original corner.