

15555

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p>Land, mountainous. Soil, rocky clay loam. Timber, fir, cedar, hemlock, maple, madrone, and oak; undergrowth, poison oak, salal, hazel, and arrowwood.</p>
	<p>From the cor. of secs. 16, 17, 20, and 21. N. 89° 19' W., bet. secs. 17 and 20. Descend 10 ft. over nearly level land.</p>
19.95	Paved road, 35 lks. wide, bears N. and S.
29.55	Paved road, 35 lks. wide, bears N. and S.
39.25	Paved road, 35 lks. wide, bears N. and S.
41.35	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in the ground, with top level with surface of ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 30 S R 5 W</p> <p>$\frac{1}{4}$ $\frac{S 17}{S 20}$</p> <p>1969</p> </div> <p>from which</p> <p>The SE. cor. of a wood pump house, 6 x 4 ft., bears N. $43\frac{1}{2}^\circ$ E., $259\frac{1}{2}$ lks. dist., long side bears N. and S.</p> <p>A power pole, 10 ins. diam., bears S. 49° E., 236 lks. dist., No. 9880.</p> <p>Ascend 55 ft. over nearly level land.</p>
52.95	Gazley Road, asphalt surfaced, 35 lks. wide, bears N. 75° W. and S. 75° E.
61.45	Gasley Road, asphalt surfaced, 35 lks. wide, bears NE. and SW.
61.75	Base of hill, bears NE. and SW.; asc. 350 ft. over SE. slope, through moderate timber and light undergrowth.
78.05	Ridge, bears N. 30° E. and S. 30° W., also dirt road, 20 lks. wide, bears same; desc. 175 ft. over SW. slope.
82.70	<p>The cor. of secs. 17, 18, 19, and 20.</p> <p>Land, mountainous and bottom land. Soil, rocky clay loam. Timber, fir, cedar, hemlock, maple, madrone, and oak; undergrowth, poison oak, salal, hazel, and arrowwood.</p>
	<p>S. $88^\circ 42'$ W., bet. secs. 18 and 19. Descend 285 ft. over NW. slope, through medium timber and light undergrowth.</p>