

15557

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

<p>CHAINS 85.03</p>	<p>The cor. of secs. 18 and 19 only, on the W. bdy. of the Tp., perpetuated and recorded by G. G. Stewart, Deputy County Surveyor, in 1921, monumented with an iron pipe, 1½ ins. diam., 30 ins. long, firmly set, projecting 8 ins. above ground, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A decayed oak stump, size indeterminate, bears S. 40° E., 200 lks. dist., no marks visible.</p> <p>and bearing trees mkd. by Stewart</p> <p style="padding-left: 40px;">A white oak, 19 ins. diam., bears N. 41° E., 109 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A white oak, 17 ins. diam., bears S. 72° W., 38½ lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A black oak, 13 ins. diam., bears N. 63° W., 102 lks. dist., with scribe mark 6 visible on opened blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 30 S</td> <td style="padding: 0 5px;">T 30 S</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 6 W</td> <td style="padding: 0 5px;">S 18</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 24</td> <td style="padding: 0 5px;">S 19</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">R 5 W</td> </tr> </table> <p>1969</p> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">An oak, 13 ins. diam., bears S. 23° E., 15 lks. dist., mkd. T30S R5W S19 BT.</p> <p style="padding-left: 40px;">Reset iron pipe alongside iron post.</p> <p>Land, mountainous and bottom land. Soil, rocky clay loam. Timber, fir, cedar, hemlock, maple, madrone, and oak; undergrowth, poison oak, salal, hazel, and arrowwood.</p>	T 30 S	T 30 S	R 6 W	S 18	S 24	S 19		R 5 W
T 30 S	T 30 S								
R 6 W	S 18								
S 24	S 19								
	R 5 W								
<p>22.95</p>	<p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 4° 25' E., bet. secs. 17 and 18.</p> <p>Descend 300 ft. along broken W. slope, through medium timber and light undergrowth.</p>								
<p>36.15</p>	<p>Bottom of descent, slopes W.; asc. 190 ft. along broken W. slope.</p>								
<p>37.05</p>	<p>Spur, slopes S. 60° W.; desc. 100 ft. over NW. slope.</p>								
<p>40.16</p>	<p>Barbed wire fence, bears E. and W.</p> <p>Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>								