

15563

T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 28 south, range 8 west, of the Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points with New Accessories when Needed."

The remonumentation of original corner points was made at the request of the Coos Bay District Manager, for administrative purposes of the Bureau of Land Management.

The mean magnetic declination is 20° E.

Subdivision, T. 28 S., R. 8 W.,
Willamette Meridian, Oregon

(Remonumenting a corner established by
George S. Pershin, Deputy Surveyor, in 1875)

The cor. of secs. 5, 6, 7 and 8, perpetuated and recorded by the Douglas County Surveyor, in 1957, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 28 S R 8 W

| | |
|---|---|
| 6 | 5 |
| 7 | 8 |

1957

from which the remains of the original bearing trees

A root hole, bears S. 50° E., 22 lks. dist., with a down yew alongside, 14 ins. diam., with scribe marks T28S R8 visible on open blaze.

A hemlock snag, 14 ins. diam., bears N. 24° W., 60 lks. dist., with scribe marks T28S R8W S6 BT visible on open blaze.

and new bearing trees

A yew, 22 ins. diam., bears N. 69° E., 139 lks. dist., mkd. T28S R8W S5 BT.

A hemlock, 12 ins. diam., bears N. 31½° W., 152 lks. dist., mkd. T28S R8W S6 BT.