

15566

Dependent Resurvey, Portion of Subdivisional Lines,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>(Restoring the survey by Dennis Hathorn, U. S. Deputy Surveyor, in 1855, the survey by Winfield S. Chapman, U. S. Deputy Surveyor, in 1875, and the survey by George S. Pershin, U. S. Deputy Surveyor, in 1875)</p> <hr/> <p>Beginning at the cor. of secs. 23, 24, 25, and 26, rehabilitated by Fred Mensch, in 1924, and not of record, monumented with an iron post, 2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 28 S R 8 W S 23 S 24 S 26 S 25 1924</p> <p>from which bearing trees mkd. by Mensch, in 1924, and not of record</p> <p>A fir, 30 ins. diam., bears S. 51½° E., 22 lks. dist., with healed blaze.</p> <p>A root hole, bears S. 48½° W., 32 lks. dist., with a down fir alongside, 18 ins. diam., with fragmentary scribe marks visible on open blaze.</p> <p>A fir, 25 ins. diam., bears N. 49½° W., 43 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1957</p> <p>A fir, 18 ins. diam., bears N. 80¾° E., 47½ lks. dist., with healed blaze.</p> <p>A fir, 20 ins. diam., bears S. 31¾° E., 34½ lks. dist., with healed blaze.</p> <p>A fir, 15 ins. diam., bears S. 39° W., 56 lks. dist., with healed blaze.</p> <p>A fir, 22 ins. diam., bears N. 49¾° W., 43 lks. dist., with healed blaze.</p> <p>Add marks 1975 to brass cap.</p> <p>S. 89° 42' W., bet. secs. 23 and 26, marking and blazing the true line.</p> <p>Ascend 40 ft. over NE. slope, through heavy timber and dense undergrowth.</p>
8.60	Top of ascent, slopes N.; desc. 5 ft. over NW. slope.
8.95	Creek, 1 lk. wide, course N. 50° E.; asc. 60 ft. over SE. slope.
17.30	Ridge, bears N. 25° E. and S. 30° W.; desc. 125 ft. over NW. slope.
27.75	Creek, 1 lk. wide, course N. 5° E.; asc. 105 ft. over NE. slope.
37.20	Ridge, bears N. and S.; desc. 5 ft. over NW. slope.