

15568

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>A cedar, 22 ins. diam., bears N. 18° E., 26 lks. dist., with healed blaze.</p> <p>A maple, 19 ins. diam., bears S. 36° E., 90 lks. dist., with healed blaze.</p> <p>A fir, 18 ins. diam., bears S. 55° W., 55 lks. dist., with healed blaze.</p> <p>A fir, 18 ins. diam., bears N. 89½° W., 69 lks. dist., with healed blaze.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, maple, oak, myrtle, alder, and chinquapin; undergrowth, salal, poison oak, Oregon grape, rhododendron, arrowwood, vine maple, and fern.</p>
	<p>N. 0° 13' W., bet. secs. 22 and 23.</p> <p>Ascend 2 ft. over SE. slope, through scattering timber and dense undergrowth.</p>
1.00	Spur, slopes N. 80° E.; desc. 205 ft. over NE. slope.
20.025	Point for the S 1/16 sec. cor. of secs. 22 and 23.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 22 S 23 1975</p> <p>from which</p> <p>A fir, 9 ins. diam., bears N. 77° E., 20 lks. dist., mkd. S 1/16 S23 BT.</p> <p>A fir, 7 ins. diam., bears N. 41½° W., 25½ lks. dist., mkd. S 1/16 S22 BT.</p> <p>Descend 40 ft. over NE. slope.</p>
23.95	Spur, slopes N. 60° E.; desc. 340 ft. over NE. slope.
29.90	Dirt road, 15 lks. wide, bears N. 35° W. and S. 25° E., curving E.
35.40	Ravine, drains N. 25° E.; asc. 2 ft. over SE. slope.
35.45	Top of ascent, slopes NE.; desc. 10 ft. over E. slope.
36.30	Ravine, drains E.; asc. 2 ft. over SE. slope.
37.10	Spur, slopes E.; desc. 10 ft. over NE. slope.
39.20	Gravelled road, 15 lks. wide, bears N. 55° E. and S. 50° W.
40.05	Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>