

Dependent Resurvey, Portion of Subdivisional Lines,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

15569

CHAINS	
	<p style="text-align: center;"> $\frac{1}{2}$ S 22 S 23 T 28 S R 8 W 1975 </p> <p>from which</p> <p>A fir, 6 ins. diam., bears N. $50\frac{1}{2}^\circ$ E., 12 lks. dist., mkd. $\frac{1}{2}$ S23 BT.</p> <p>A white fir, 6 ins. diam., bears N. 79° W., 20 lks. dist., mkd. $\frac{1}{2}$ S22 BT.</p> <p>Descend 35 ft. over NE. slope.</p>
41.35	Creek, 1 lk. wide, course N. 50° E.; asc. 10 ft. over SE. slope.
42.20	Spur, slopes N. 45° E.; desc. 10 ft. over NE. slope.
43.70	Ravine, drains N. 85° E.; asc. 25 ft. over SE. slope.
47.80	Spur, slopes N. 85° E.; desc. 15 ft. over NE. slope.
49.05	Creek, 1 lk. wide, course S. 80° E.; asc. 80 ft. over SE. slope.
57.30	Spur, slopes N. 60° E.; desc. 35 ft. over NE. slope.
60.075	Point for the N $1/16$ sec. cor. of secs. 22 and 23.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;"> N $1/16$ S 22 S 23 1975 </p> <p>from which</p> <p>A chinquapin, 8 ins. diam., bears S. $79\frac{1}{2}^\circ$ E., 33 lks. dist., mkd. N $1/16$ S23 BT.</p> <p>A hemlock, 10 ins. diam., bears N. 63° W., $32\frac{1}{2}$ lks. dist., mkd. N $1/16$ S22 BT.</p> <p>Descend 295 ft. over NE. slope.</p>
62.80	Slope changes to NW.
71.45	Tenmile Creek, 10 lks. wide, course N. 65° E.; asc. 20 ft. over SE. slope.
73.05	Leave timber, enter open field, edge bears N. 40° W. and S. 70° E.
80.10	The cor. of secs. 14, 15, 22, and 23, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1957, from original evidence no longer in existence, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	<p style="text-align: center;"> COUNTY SURVEYORS OFFICE T 28 S R 8 W S 15 S 14 S 22 S 23 1957 </p>