

Dependent Resurvey, Portion of Subdivisional Lines, **15571**  
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 16 ins. diam., bears S. 4° E., 85½ lks. dist., with healed blaze.</p> <p>A fir, 15 ins. diam., bears S. 57° W., 92 lks. dist., with scribe marks T28S R8W S23 CS BT visible on open blaze.</p> <p>and a new bearing tree</p> <p>A fir, 6 ins. diam., bears N. 76½° W., 51½ lks. dist., mkd. T28S R8W S14 BT.</p> <p>N. 89° 57' W., bet. secs. 14 and 23.</p> <p>Descend 390 ft. over NW. slope, through scattering timber and dense undergrowth.</p>
5.55	Dirt road, 15 lks. wide, bears N. and S. 5° W.
7.30	Gravelled road, 20 lks. wide, bears N. 20° E., curving N., and S. 25° W., curving S.
10.90	Gravelled road, 40 lks. wide, bears N. 5° W. and S. 15° E., in curve.
17.45	Gravelled road, 15 lks. wide, bears N. 40° E. and S. 40° W.
18.20	Creek, 15 lks. wide, course S. 30° W.; asc. 300 ft. over SE. slope.
20.25	Gravelled road, 15 lks. wide, bears N. 15° E. and S. 15° W.
36.75	Ridge, bears N. 5° E. and S. 20° W.; desc. 20 ft. over SW. slope.
39.30	Ravine, drains S. 10° W.; desc. 10 ft. over SW. slope.
40.22	<p>Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\frac{1}{4} \frac{S 14}{S 23}</math> <p>T 28 S R 8 W 1975</p> </div> <p>from which</p> <p>A fir, 9 ins. diam., bears N. 54¾° E., 30 lks. dist., mkd. ¼ S14 BT.</p> <p>A fir, 10 ins. diam., bears S. 60½° E., 18 lks. dist., mkd. ¼ S23 BT.</p> <p>Ascend 45 ft. over SE. slope.</p>
41.60	Ridge, bears N. 10° E. and S. 5° E.; desc. 30 ft. over SW. slope.
43.05	Ravine, drains S. 10° W.; asc. 60 ft. over SE. slope.
46.10	Spur, slopes S. 10° E.; desc. 340 ft. over SW. slope.