

Dependent Resurvey, Portion of Subdivisional Lines,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

15573

CHAINS	
	<p>A fir, 16 ins. diam., bears S. 16° W., 28½ lks. dist., with healed upper blaze and scribe marks CS BT visible on lower bark blaze.</p> <p>A fir, 21 ins. diam., bears N. 73° W., 72 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Shaner</p> <p>A fir, 16 ins. diam., bears N. 22° E., 42 lks. dist., with scribe marks T28S R8W S34 BT visible on open blaze.</p> <p>A white fir, 8 ins. diam., bears S. 88° E., 63 lks. dist., with scribe marks T29S R8W S3 BT visible on open blaze.</p> <p>N. 0° 19' W., bet. secs. 33 and 34.</p> <p>Descend 215 ft. over NE. slope, through scattering timber and dense undergrowth.</p>
4.75	Ravine, drains S. 85° E.; asc. 75 ft. over SE. slope.
10.65	Spur, slopes N. 60° E.; desc. 5 ft. over NE. slope.
11.30	Ravine, drains E.; asc. 25 ft. over SE. slope.
12.50	Spur, slopes N. 80° E.; desc. 180 ft. over NW. slope.
15.80	Ravine, drains N. 15° E.; desc. 165 ft. over NE. slope.
22.35	Spur, slopes N. 60° E.; desc. 55 ft. over N. slope.
23.55	Ravine, drains N. 80° E.; asc. 30 ft. over SE. slope.
26.15	Spur, slopes N. 60° E.; desc. 135 ft. over NE. slope.
32.35	Creek, 3 lks. wide, course N. 70° E.; asc. 235 ft. over broken S. slope.
35.05	Dirt road, 20 lks. wide, bears N. 60° W. and S. 60° E.
39.58	<p>Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 33 S 34 T 28 S R 8 W 1975 </p> <p>from which</p> <p>A cedar, 12 ins. diam., bears S. 38½° E., 62 lks. dist., mkd. ¼ S34 BT.</p> <p>A fir, 13 ins. diam., bears N. 11½° W., 45½ lks. dist., mkd. ¼ S33 BT.</p> <p>Ascend 325 ft. over broken S. slope.</p>
46.40	Dirt road, 20 lks. wide, bears N. 60° W. and S. 60° E.