

15574

Dependent Resurvey, Portion of Subdivisional Lines,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

| | | | | | | |
|-----------------|---|--------------|-------------|-------------|-------|------|
| CHAINS 60.00 | Ridge, bears N. 50° W., and S. 75° E.; desc. 365 ft. over NE. slope. | | | | | |
| 64.35 | Ravine, drains E.; asc. 50 ft. over SE. slope. | | | | | |
| 67.75 | Spur, slopes S. 70° E.; desc. 155 ft. over NE. slope. | | | | | |
| 72.35 | Ravine, drains N. 85° E.; asc. 20 ft. over SE. slope. | | | | | |
| 75.50 | Spur, slopes S. 80° E.; desc. 25 ft. over NE. slope. | | | | | |
| 79.16 | <p>The cor. of secs. 27, 28, 33, and 34, determined at record bearing and distance from the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A sawed fir stump, 28 ins. diam., bears S. 85° E., 53 lks. dist., with scribe marks BT visible on opened lower blaze.</p> <p style="padding-left: 40px;">A fir root crown, 35 ins. diam., bears N. 85° W., 57 lks. dist., with a down fir alongside, no marks visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 28 S R 8 W</td></tr> <tr><td> S 28 S 27</td></tr> <tr><td> S 33 S 34</td></tr> <tr><td> 1975</td></tr> </table> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A white fir, 5 ins. diam., bears N. 67½° E., 4 lks. dist., mkd. T28S R8W S27 BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 38½° E., 22½ lks. dist., mkd. T28S R8W S34 BT.</p> <p style="padding-left: 40px;">A hemlock, 8 ins. diam., bears S. 30¾° W., 34½ lks. dist., mkd. T28S R8W S33 BT.</p> <p style="padding-left: 40px;">A white fir, 6 ins. diam., bears N. 83° W., 38 lks. dist., mkd. T28S R8W S28 BT.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, maple, oak, myrtle, alder, and chinquapin; undergrowth, salal, poison oak, vine maple, Oregon grape, rhododendron, and fern.</p> | T 28 S R 8 W | S 28 S 27 | S 33 S 34 | 1975 | |
| T 28 S R 8 W | | | | | | |
| S 28 S 27 | | | | | | |
| S 33 S 34 | | | | | | |
| 1975 | | | | | | |
| | <p>From the ¼ sec. cor. of secs. 27 and 34, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1957, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>COUNTY SURVEYORS OFFICE</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 28 S</td></tr> <tr><td> ½ S 27</td></tr> <tr><td> S 34</td></tr> <tr><td>R 8 W</td></tr> <tr><td>1957</td></tr> </table> </div> | T 28 S | ½ S 27 | S 34 | R 8 W | 1957 |
| T 28 S | | | | | | |
| ½ S 27 | | | | | | |
| S 34 | | | | | | |
| R 8 W | | | | | | |
| 1957 | | | | | | |