

Dependent Resurvey, Portion of Subdivisional Lines,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

15575

CHAINS	
	<p>from which the remains of the original bearing trees</p> <p>A fir, 45 ins. diam., bears N. 30° E., 6 lks. dist., with healed lower blaze. (Rescribed $\frac{1}{4}$ S27 CS BT on bark, by Byron)</p> <p>and a bearing tree mkd. by Byron</p> <p>A cedar, 25 ins. diam., bears S. 58$\frac{1}{2}$° W., 91$\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S34 CS BT visible on bark blaze.</p> <p>S. 89° 09' W., bet. secs. 27 and 34.</p> <p>Ascend 45 ft. over SE. slope, through scattering timber and dense undergrowth.</p>
3.60	Spur, slopes S. 55° E.; asc. 180 ft. over SE. slope.
12.60	Ridge, bears N. 20° E. and S. 55° W.; desc. 275 ft. over SW. slope.
22.65	Ravine, drains S. 40° W.; asc. 5 ft. over SE. slope.
24.85	Spur, slopes S. 10° W.; desc. 215 ft. over SW. slope.
36.65	Dirt road, 15 lks. wide, bears N. 25° W. and S. 25° E.
38.05	Muns Creek, 6 lks. wide, course S. 35° E.; asc. 65 ft. over NE. slope.
40.02	The cor. of secs. 27, 28, 33, and 34.
	<p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, oak, maple, myrtle, alder, and chinquapin; undergrowth, salal, poison oak, vine maple, Oregon grape, rhododendron, and fern.</p>
	<p>N. 0° 42' W., bet. secs. 27 and 28.</p> <p>Descend 60 ft. over NE. slope, through scattering timber and dense undergrowth.</p>
3.40	Muns Creek, 4 lks. wide, course S. 35° E.; asc. 145 ft. over SW. slope.
6.80	Dirt road, 25 lks. wide, bears N. 20° W. and S. 20° E.
13.40	Spur, slopes S. 45° W.; desc. 2 ft. over NW. slope.
14.50	Ravine, drains S. 45° W.; asc. 90 ft. over broken S. slope.
20.95	Spur, slopes S. 40° W.; desc. 10 ft. over NW. slope.
23.85	Creek, 2 lks. wide, course N. 80° W.; asc. 285 ft. over SW. slope.
40.18	The $\frac{1}{2}$ sec. cor. of secs. 27 and 28, perpetuated and recorded by Howard Johnstone, RLS No. 498, in 1962, further perpetuated by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron post, 1 $\frac{1}{2}$ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.