

15580 Dependent Resurvey, Portion of Subdivisional Lines,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	Ascend 285 ft. over SE. slope, through scattered timber and dense undergrowth.
19.12	Point for the N 1/16 sec. cor. of secs. 28 and 29. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> N 1/16 S 29 S 28 1975 </div> from which A white fir, 8 ins. diam., bears S. 83½° E., 13 lks. dist., mkd. N 1/16 S28 BT. A fir, 8 ins. diam., bears S. 34½° W., 48 lks. dist., mkd. N 1/16 S29 BT. Descend 10 ft. over SE. slope.
20.70	Ravine, drains S. 50° E.; asc. 10 ft. over SE. slope.
21.40	Spur, slopes S. 40° E.; desc. 10 ft. over NE. slope.
22.05	Ravine, drains S. 20° E.; asc. 365 ft. over SW. slope.
35.00	Spur, slopes S. 80° E.; desc. 105 ft. over NE. slope.
38.24	The cor. of secs. 20, 21, 28, and 29, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1957, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. <div style="text-align: center;"> COUNTY SURVEYORS OFFICE T 28 S R 8 W S 20 S 21 S 29 S 28 1957 </div> from which the remains of the original bearing trees A fir, 55 ins. diam., bears N. 10° E., 30½ lks. dist., rescribed by Byron with scribe marks T28S S21 CS visible on open blaze. (Record, 27 lks., to face) A fir, 40 ins. diam., bears S. 30° E., 38 lks. dist., with scribe marks BT visible on partially open blaze. and the remains of bearing trees mkd. by Byron A fir snag, 10 ins. diam., bears S. 47° E., 63 lks. dist., with scribe marks T28S R8W S28 CS BT visible on open double blaze. A chinquapin, 10 ins. diam., bears S. 34½° W., 39 lks. dist., with scribe marks S29 CS BT visible on partially open double blaze. (Record, 37 lks.) A maple, 10 ins. diam., bears N. 16° W., 20 lks. dist., with healed double blaze. Land, mountainous. Soil, rocky clay.