

15584

Dependent Resurvey, Portion of Subdivisional Lines,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
57.85	Spur, slopes N. 40° E.; desc. 10 ft. over NW. slope.
58.25	Creek, 3 lks. wide, course N. 30° E.; asc. 55 ft. over NE. slope.
59.05	Dirt road, 15 lks. wide, bears N. 35° E. and S. 35° W.
62.60	Spur, slopes N. 40° E.; desc. 10 ft. over NW. slope.
63.45	Creek, 2 lks. wide, course N. 40° E.; asc. 200 ft. over SE. slope.
68.10	Leave timber, enter old logged area, edges bear S. 55° E. and W.
74.20	Spur, slopes S. 30° E.; desc. 2 ft. over SW. slope.
75.30	Creek, 1 lk. wide, course S. 10° E.; asc. 60 ft. over broken E. slope.
80.80	The cor. of secs. 16, 17, 20, and 21.
	Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, maple, oak, myrtle, alder, and chinquapin; undergrowth, salal, poison oak, Oregon grape, vine maple, rhododendron, and fern.
	N. 0° 12' W., bet. secs. 16 and 17.
	Descend 30 ft. over NE. slope, through scattering timber and dense undergrowth.
5.20	Ravine, drains N. 30° E.; asc. 5 ft. over SE. slope.
7.90	Spur, slopes E.; desc. 10 ft. over NE. slope.
9.40	Ravine, drains S. 85° E.; asc. 110 ft. over SE. slope.
18.60	Spur, slopes S. 70° E.; desc. 20 ft. over NE. slope.
21.45	Bottom of descent, slopes E.; asc. 25 ft. over SE. slope.
28.15	Spur, slopes N. 70° E.; desc. 110 ft. over NE. slope.
37.25	Paved road, 40 lks. wide, bears N. 40° W. and S. 45° E.
38.55	Ravine, drains S. 80° E.; asc. 25 ft. over SE. slope.
40.74	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$ S 17 S 16 T 28 S R 8 W 1975
	from which
	A hemlock, 8 ins. diam., bears N. 37° E., 49 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S16 BT.