

Dependent Resurvey, Portion of Subdivisional Lines,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

15585

CHAINS	
	A fir, 17 ins. diam., bears S. $63\frac{1}{2}^{\circ}$ W., 55 lks. dist., mkd. $\frac{1}{4}$ S17 BT.
	Ascend 10 ft. over SE. slope.
41.15	Spur, slopes N. 55° E.; desc. 40 ft. over NE. slope.
43.60	Creek, 4 lks. wide, course N. 75° E.; asc. 380 ft. over SE. slope.
48.30	Dirt road, 20 lks. wide, bears N. 50° E. and S. 50° W.
55.70	Ridge, bears N. 80° E. and S. 80° W.; desc. 365 ft. over NE. slope.
57.85	Power transmission line, bears E. and W.
62.15	Dirt road, 15 lks. wide, bears N. 75° W. and S. 60° E.
70.90	Ravine, drains N. 30° E.; desc. 75 ft. over NE. slope.
74.05	Top of ascent, slopes E.; desc. 35 ft. over NW. slope.
74.15	Creek, 6 lks. wide, course N. 15° E.; desc. 85 ft. over NE. slope.
79.55	Creek, 8 lks. wide, course S. 65° E.; asc. 120 ft. over S. slope.
81.48	The cor. of secs. 8, 9, 16, and 17, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1957, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE T 28 S S 8 S 9 S 17 S 16 R 8 W 1957
	from which the original bearing trees
	A hemlock, 11 ins. diam., bears N. $16\frac{1}{2}^{\circ}$ E., 10 lks. dist., with healed blaze. Rescribed by Byron with scribe marks 28S R8W BT visible on partially open double blaze.
	A fir, 65 ins. diam., bears S. 62° E., 19 lks. dist., with scribe marks T28 S visible on bark blaze. Rescribed by Byron with scribe marks T28S R8W S16 CS BT visible on bark blaze. (Record, 16 lks.)
	A hemlock, 21 ins. diam., bears S. 69° W., 25 lks. dist., no marks visible on partially open blaze. Rescribed by Byron with scribe marks T28S R8W S17 C visible on partially open double blaze.
	A hemlock, 30 ins. diam., bears N. $45\frac{1}{2}^{\circ}$ W., 31 lks. dist., with scribe marks BT visible on partially open blaze. Rescribed by Byron, with healed double blaze.
	Land, mountainous. Soil, rocky clay.