

058

15588

Dependent Resurvey, Portion of Subdivisional Lines,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

FOOK PER HINTZ
DEC 1986 M103-8

| |
|------------|
| T 28 S |
| S 4 S 3 |
| S 9 S 10 |
| R 8 W |
| 1961 |

from which the remains of the original bearing trees

A fir stump, 32 ins. diam., bears N. 53° E., 70 lks. dist., with scribe marks 28S R8W S3 visible on bark blaze.

A fir stump, 45 ins. diam., bears S. 4½° E., 22 lks. dist., no marks visible.

and the remains of bearing trees mkd. by Byron

A hemlock, 15 ins. diam., bears N. 57° E., 96 lks. dist., with healed blaze.

A fir stump, 12 ins. diam., bears S. 15½° E., 28 lks. dist., with fragmentary scribe marks visible on open blaze.

A hemlock, 13 ins. diam., bears S. 44° W., 96 lks. dist., with scribe marks 8S R8W S9 CS B visible on open blaze.

A hemlock, 36 ins. diam., bears N. 84° W., 48 lks. dist., with scribe marks T28S R8W S4 CS BT visible on open blaze.

and a new bearing tree

A fir, 20 ins. diam., bears S. 40½° E., 201 lks. dist., mkd. T28S R8W S10 BT.

N. 89° 36' W., bet. secs. 4 and 9.

Descend 20 ft. over NW. slope, through scattering timber and dense undergrowth.

- 1.25 Ravine, drains N. 15° W.; asc. 60 ft. over NE. slope.
- 4.55 Spur, slopes N. 30° W.; desc. 145 ft. over NW. slope.
- 17.10 Ravine, drains S. 60° W.; asc. 2 ft. over SE. slope.
- 17.50 Spur, slopes S. 50° W.; desc. 700 ft. over SW. slope.
- 41.71 Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

FOOK PER HINTZ
DEC 1986 M103-8

| | |
|--------------|-----|
| ¼ | S 4 |
| | S 9 |
| T 28 S R 8 W | |
| 1975 | |

from which

A fir, 17 ins. diam., bears N. 44° E., 17 lks. dist., mkd. ¼ S4 BT.