

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

15599

CHAINS	
52.10	Spur, slopes S. 70° W.; desc. 50 ft. over NW. slope.
57.05	Ravine, drains S. 80° W.; asc. 20 ft. over SW. slope.
58.50	Spur, slopes S. 80° W.; desc. 65 ft. over NW. slope.
65.55	Ravine, drains N. 80° W.; asc. 50 ft. over SW. slope.
71.15	Spur, slopes N. 70° W.; desc. 145 ft. over NW. slope.
77.48	Point for the cor. of secs. 3, 4, 9, and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 7 W
S 4 S 3
S 9 S 10
1975

Fl. by B. HOLT
1/13/84
SEE CS. 58/290

from which

A fir, 9 ins. diam., bears N. 3½° E., 31 lks. dist., mkd. T30S R7W S3 BT.

A fir, 9 ins. diam., bears S. 63° E., 45 lks. dist., mkd. T30S R7W S10 BT.

A fir, 11 ins. diam., bears S. 60° W., 45½ lks. dist., mkd. T30S R7W S9 BT.

A fir, 8 ins. diam., bears N. 81¾° W., 64 lks. dist., mkd. T30S R7W S4 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, oak, myrtle, alder, and chinquapin; undergrowth, salal, poison oak, vine maple, rhododendron, and fern.

From the ¼ sec. cor. of secs. 3 and 10, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1965, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S
¼ S 3
S 10
R 7 W
1965

from which the remains of the original bearing trees

A fir, 40 ins. diam., bears N. 42° E., 25 lks. dist., with scribe marks ¼ B visible on bark blaze.

and bearing trees mkd. by Byron

A hemlock, 15 ins. diam., bears N. 22½° E., 33½ lks. dist., with scribe marks ¼ S3 CS visible on open double blaze.