

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

15601

CHAINS

- 38.30 Thompson Creek, 20 lks. wide, course W.; asc. 15 ft. over SE. slope.
- 38.83 The $\frac{1}{4}$ sec. cor. of secs. 3 and 4, monumented with the original sandstone, 12 x 8 x 8 ins., firmly set, 8 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, from which the original bearing trees:
- A live oak, 13 ins. diam., bears S. 62° E., 35 lks. dist., with axe marks visible on opened blaze.
- A live oak, 12 ins. diam., bears S. 45° W., 16 lks. dist., with fragmentary scribe marks visible on opened blaze. (Record, S. 54° W.)
- At the corner point
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 18 ins. in the ground, to bedrock, mkd. X, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
- $\frac{1}{4}$
S 4 | S 3
T 30 S R 7 W
1975
- from which new bearing trees
- A fir, 10 ins. diam., bears N. 69 $\frac{1}{2}$ ° E., 83 lks. dist., mkd. $\frac{1}{4}$ S3 BT.
- A fir, 6 ins. diam., bears N. 48° W., 97 lks. dist., mkd. $\frac{1}{4}$ S4 BT.
- Deposit corner stone alongside iron post.
-
- N. 0° 16' E., beginning new measurement.
- 8.85 Top of bluff, faces S., edge bears E. and W.
- 16.60 Spur, slopes N. 85° W.; desc. 15 ft. over NW. slope.
- 17.70 Ravine, drains S. 75° W.; asc. 180 ft. over SW. slope.
- 28.55 Spur, slopes S. 60° W.; desc. 90 ft. over NW. slope.
- 39.47 The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., perpetuated by James W. Byron, Deputy County Surveyor, in 1962, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 10 ins. above ground, with the remains of the iron post set by Mensch, in 1924, alongside, cap mkd. as described in the official record, from which the remains of the original bearing trees:
- A root hole, bears S. 25° E., 5 lks. dist., with a down pine alongside, 8 ins. diam., with axe marks visible on decayed blaze.
- A root hole, bears S. 15° W., 5 lks. dist., with a down pine alongside, 10 ins. diam., with axe marks visible on decayed blaze.
- A pine, 28 ins. diam., bears N. 54° W., 16 lks. dist., no marks visible on decayed blaze. (Record, N. 60° W.)
- and the remains of bearing trees mkd. by Mensch