

15602

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A root hole, bears N. 41° E., 65 lks. dist.

A pine snag, 18 ins. diam., bears S. 66° W., 39 lks. dist., with healed blaze.

and bearing trees mkd. by Byron

A pine, 24 ins. diam., bears N. 19° E., 38 lks. dist., with fragmentary scribe marks visible on partially open double blaze.

A white fir, 10 ins. diam., bears S. 6½° E., 16½ lks. dist., with healed double blaze.

A fir, 8 ins. diam., bears S. 70° W., 29 lks. dist., with healed double blaze.

A cedar, 12 ins. diam., bears N. 72° W., 28½ lks. dist., with scribe marks 29½S R7W S33 CS BT visible on open double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29½ S R 7 W  
S 33 | S 34  
S 4 | S 3  
T 30 S  
1975

from which a new bearing tree

A fir, 9 ins. diam., bears N. 33° E., 48 lks. dist., mkd. T29½S R7W S34 BT.

Reset old iron post and iron pipe alongside iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, oak, myrtle, alder, and chinquapin; undergrowth, salal, vine maple, Oregon grape, rhododendron, poison oak, and fern.

From the cor. of secs. 8, 9, 16, and 17, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1965, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S  
S 8 | S 9  
S 17 | S 16  
R 7 W  
1965

from which the remains of the original bearing trees

A fir, 38 ins. diam., bears N. 71° E., 72 lks. dist., with scribe marks T3 R W 9 visible on bark blaze.

A fir, 39 ins. diam., bears S. 15° E., 7 lks. dist., with scribe marks T30S R7W S16 BT visible on bark blaze.