

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir stump, 38 ins. diam., bears N. 18° W., 60 lks. dist., no marks visible.</p> <p>and a bearing tree mkd. by Byron</p> <p>A madrone, 14 ins. diam., bears S. 79° W., 37 lks. dist., with scribe marks 30S R7W S17 CS BT visible on open blaze.</p> <p>N. 0° 55' E., bet. secs. 8 and 9.</p> <p>Descend 855 ft. over NE. slope, through clear cut area.</p>
29.85	Creek, 1 lk. wide, course N. 65° E.; asc. 2 ft. over SE. slope.
31.35	Spur, slopes N. 45° E.; desc. 135 ft. over NE. slope.
38.00	Creek, 2 lks. wide, course N. 75° W.; desc. 2 ft. over NW. slope.
38.74	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 8 S 9 T 30 S R 7 W 1975 </p> <p>from which</p> <p>A fir, 5 ins. diam., bears S. 32° E., $77\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S9 BT.</p> <p>A fir, 5 ins. diam., bears S. $74\frac{1}{2}$° W., 60 lks. dist., mkd. $\frac{1}{4}$ S8 BT.</p> <p>Descend 35 ft. over NW. slope.</p>
40.90	Gravelled road, 40 lks. wide, bears N. 85° E. and W., in curve.
42.75	Creek, 1 lk. wide, course W., asc. 495 ft. over SW. slope.
57.55	Spur, slopes W.; desc. 5 ft. over NW. slope.
58.11	<p>Point for the N $\frac{1}{16}$ sec. cor. of secs. 8 and 9.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> N $\frac{1}{16}$ S 8 S 9 1975 </p> <p>from which</p> <p>A fir, 8 ins. diam., bears N. $38\frac{1}{2}$° E., 28 lks. dist., mkd. N $\frac{1}{16}$ S9 BT.</p> <p>A fir, 8 ins. diam., bears N. $55\frac{1}{2}$° W., $19\frac{1}{2}$ lks. dist., mkd. N $\frac{1}{16}$ S8 BT.</p>