

15604

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS									
	<p>Descend 60 ft. over NW. slope.</p>								
67.10	<p>Ridge, bears N. 20° W. and S. 20° E.; desc. 295 ft. over steep NE. slope.</p>								
77.48	<p>The cor. of secs. 4, 5, 8, and 9, determined at record bearing and distance from the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A madrone, 35 ins. diam., bears S. 30° E., 31 lks. dist., with axe marks visible on decayed double blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 30 S R 7 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">5</td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">4</td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">8</td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">9</td> </tr> </table> <p>1975</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 83¾° E., 44½ lks. dist., mkd. T30S R7W S4 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 81¼° E., 31 lks. dist., mkd. T30S R7W S9 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 81¼° W., 33 lks. dist., mkd. T30S R7W S8 BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 53¾° W., 29 lks. dist., mkd. T30S R7W S5 BT.</p> <p>Corner is further substantiated by old N., S., and W. blazed line. Blazed line going N. from corner has been dated by ring count to approximately 1892. The S. and W. blazed lines look very old but are bark blazed.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, maple, oak, myrtle, alder, and chinquapin; undergrowth, salal, Oregon grape, vine maple, rhododendron, poison oak, and fern.</p>	S	5	S	4	S	8	S	9
S	5	S	4						
S	8	S	9						
	<p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>S. 88° 15' W., bet. secs. 4 and 9.</p> <p>Descend 330 ft. over NW. slope, through heavy timber and dense undergrowth.</p>								
12.20	<p>Spur, slopes N. 30° W.; desc. 105 ft. over NW. slope.</p>								
19.20	<p>Point for the E 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16 <table style="display: inline-table; vertical-align: middle;"> <tr> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">4</td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">9</td> </tr> </table></p> <p>1975</p> </div> <p>from which</p>	S	4	S	9				
S	4								
S	9								