

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

15607

CHAINS	
	$\frac{1}{4} \frac{S \ 5}{S \ 8}$ <p>T 30 S R 7 W 1975</p> <p>from which</p> <p>A fir, 10 ins. diam., bears N. 18$\frac{1}{2}$° W., 59 lks. dist., mkd. $\frac{1}{4}$ S5 BT.</p> <p>A fir, 7 ins. diam., bears South, 29$\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S8 BT.</p> <p>Descend 165 ft. over NW. slope.</p> <p>54.95 Ravine, drains N. 70° W.; asc. 20 ft. over NE. slope.</p> <p>56.45 Spur, slopes N. 25° W.; desc. 315 ft. over NW. slope.</p> <p>65.75 Diversion ditch, 5 ft. wide, bears N. 30° E. and S. 30° W.</p> <p>67.60 Olalla Creek, 25 lks. wide, course N. 35° E.; asc. 325 ft. over broken E. slope.</p> <p>73.75 Gravelled road, 40 lks. wide, bears N. 10° E. and S. 10° W.</p> <p>77.96 The cor. of secs. 5, 6, 7, and 8, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1964, monumented with a rebar, 5/8 in. diam., firmly set, projecting 8 ins. above ground, from which the original bearing trees:</p> <p>A cedar, 20 ins. diam., bears N. 58° E., 77 lks. dist., with scribe marks 7W visible on open blaze.</p> <p>A madrone, 35 ins. diam., bears S. 28° E., 62 lks. dist., no marks visible on open double blaze.</p> <p>A cedar, 45 ins. diam., bears S. 30° W., 74 lks. dist., with scribe marks 7 S visible on partially open blaze.</p> <p>A cedar, 45 ins. diam., bears N. 32° W., 30 lks. dist., with healed blaze.</p> <p>and a bearing tree not of record</p> <p>A fir, 15 ins. diam., bears S. 5° E., 50 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{c} T \ 30 \ S \ R \ 7 \ W \\ S \ 6 \ \ S \ 5 \\ S \ 7 \ \ S \ 8 \\ 1975 \end{array}$ <p>from which a new bearing tree</p> <p>A fir, 10 ins. diam., bears S. 24$\frac{1}{2}$° W., 19$\frac{1}{2}$ lks. dist., mkd. T30S R7W S7 BT.</p>