

15610

T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and subdivision of section 15, township 29 south, range 3 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey, is as follows:

A portion of the subdivisional lines was surveyed by Dennis Hathorn, in 1857.

The subdivision of the township was completed by William H. Byars, in 1881.

A portion of the subdivisional lines was resurveyed by Donald R. Beck, in 1964-65.

A portion of the subdivisional lines was resurveyed by John M. Jelley and Lynn M. Roseberry, in 1965-67.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions, dated November 1, 1974, for Group Number 857, Oregon.

The directions of the lines were determined by deflection angles obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming closures were measured twice to preclude error. Only those lines bounding or crossing public lands were blazed.

The geographic position of the corner of sections 14, 15, 22, and 23, as scaled from the Dixonville, Oregon, quadrangle map, published by the United States Geological Survey, in 1954, is as follows:

Latitude $43^{\circ} 02.5' N.$ Longitude $123^{\circ} 02.4' W.$

The mean magnetic declination is $20^{\circ} E.$

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 29 S., R. 3 W., Willamette Meridian, Oregon

(Restoring the survey by Dennis Hathorn,
U. S. Deputy Surveyor, in 1857,
the survey by William H. Byars,
U. S. Deputy Surveyor, in 1881,
and the resurvey by Donald R. Beck,
Cadastral Surveyor, in 1964-65)

Beginning at the cor. of secs. 14, 15, 22, and 23, perpetuated and recorded by John H. Markham, Jr., Professional Engineer, No. 2880, in 1950, monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, from which the remains of the original bearing trees: