

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Meridian, Oregon


15612

CHAINS

A cedar, 21 ins. diam., bears S. 66° E., 44 lks.
dist., mkd. $\frac{1}{4}$ S14 BT.

A fir, 8 ins. diam., bears S. 34° W., 104 lks.
dist., mkd. $\frac{1}{4}$ S15 BT.

From this point, a local witness cor., established by
James W. Byron, Deputy County Surveyor, in 1962, bears
North, $4\frac{1}{2}$ lks. dist., monumented with an iron post, $1\frac{1}{4}$
ins. diam., firmly set, projecting 12 ins. above ground,
with brass cap mkd.



from which bearing trees mkd. by Byron

A cedar, 12 ins. diam., bears S. 46° E., 19 lks.
dist., with scribe marks $\frac{1}{4}$ S14 WC CS visible
on partially healed blaze.

A cedar, 20 ins. diam., bears N. 71° W., 44 lks.
dist., with fragmentary scribe marks visible on
partially healed blaze.

N. 0° 21' E., beginning new measurement.

Descend 235 ft. over NW. slope.

- 7.25 Dirt road, 20 lks. wide, bears S. 20° E. and N. 33° W.,
15.15 Dirt road, 20 lks. wide, bears S. 30° W. and N. 5° E.
19.82 Point for the N 1/16 sec. cor. of sec. 15 only.

Set an iron post, 28 ins. long, $2\frac{1}{4}$ ins. diam., 20 ins.
in the ground, with brass cap mkd.

N 1/16	
S 15	
1975	

from which

A fir, 8 ins. diam., bears S. 47° W., 54 lks.
dist., mkd. N 1/16 S15 BT.

A fir, 8 ins. diam., bears N. 60° W., 40 lks.
dist., mkd. N 1/16 S15 BT.

Descend 180 ft. over NW. slope.

- 25.85 Creek, 3 lks. wide, course N. 60° W.; asc. 45 ft. over
SW. slope.
27.25 Spur, slopes W.; desc. 30 ft. over NW. slope.
29.15 Creek, 2 lks. wide, course S. 45° W.; asc. 240 ft. over
SE. slope.
33.50 Dirt road, bears N. 55° E. and S. 55° W.