

15613

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS
39.60

The cor. of secs. 11 and 14 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 29 S R 3 W
S 15 | S 11
 | S 14
1964

from which the remains of the original bearing trees

A root hole, bears N. 55° E., 31 lks. dist., with a down fir alongside, 23 ins. diam., with scribe marks T29S R3W S11 CS BT visible on bark blaze.

A fir stump, 24 ins. diam., bears S. 35° E., 25 lks. dist., with fragmentary scribe marks visible on partially decayed blaze.

and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1957

A cedar, 16 ins. diam., bears S. 25½° E., 35 lks. dist., with healed blaze.

A cedar stump, 17 ins. diam., bears N. 12½° W., 39 lks. dist., with scribe marks T29S R3W S15 CS BT visible on open blaze.

and a bearing tree mkd. by Byron, in 1962

A fir snag, 16 ins. diam., bears N. 1½° E., 21 lks. dist., with scribe marks T29S R3W S15 CS BT visible on open blaze.

and a new bearing tree

A fir, 24 ins. diam., bears N. 30° E., 131 lks. dist., mkd. T29S R3W S11 BT.

N. 1° 48' E., beginning new measurement.

Ascend 120 ft. over SE. slope, along E. edge of logged area.

5.00 Enter scattered timber and light undergrowth, edges bear S. and W.

5.70 Spur, slopes S. 50° W.; continue over spur.

6.11 The closing cor. of secs. 10 and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 29 S
C S 10 | S 11
C S 15 |
R 3 W
1965

from which bearing trees mkd. by Beck, in 1965

A fir, 12 ins. diam., bears S. 75° W., 45 lks. dist., with healed blaze. (Record, S. 78° W.)

A fir, 10 ins. diam., bears N. 36° W., 29 lks. dist., with healed blaze. (Record, N. 33½° W.)