

15615

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
6.65	Ridge, bears N. 50° E. and S. 50° W.; desc. 465 ft. over NW. slope, enter heavy timber, edge bears same.
15.35	Dirt road, 15 lks. wide, bears N. 55° E. and S. 55° W.
17.10	Enter logged area, edges bear S. and W.
19.85	Enter land slide, edge bears N. and S.
21.75	Leave land slide, edge bears N. and S.
25.05	Ravine, drains N. 12° E.; asc. 100 ft. over NE. slope.
28.95	Spur, slopes N. 10° W.; desc. 155 ft. over NW. slope.
34.25	Ravine, drains N.; asc. 70 ft. over NE. slope.
37.40	The cor. of secs. 15, 16, 21, and 22, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1961, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 29 S
 S 16 | S 15
 S 21 | S 22
 R 3 W
 1961

from which the remains of the original bearing trees

A cedar, 24 ins. diam., bears N. 80° E., 70 lks. dist., no marks visible on decayed blaze.

A fir snag, 36 ins. diam., bears S. 75° E., 16 lks. dist., no marks visible. (Record, 10 lks.)

A cedar stump, 36 ins. diam., bears S. 65° W., 69 lks. dist., no marks visible. (Record, 71 lks.)

A fir stump, 36 ins. diam., bears N. 5° W., 53 lks. dist., with healed blaze. (Record, 56 lks.)

and bearing trees mkd. by Byron

A fir, 16 ins. diam., bears N. 84° E., 33 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A pine, 22 ins. diam., bears S. 46° E., 84 lks. dist., with healed blaze.

A fir, 18 ins. diam., bears S. 62° W., 47 lks. dist., with healed blaze.

A fir, 18 ins. diam., bears N. 51° W., 14 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, pine, madrone, maple, oak, alder, and dogwood; undergrowth, salal, fern, vine maple, poison oak, huckleberry, hazel, arrowwood, and Oregon grape.

N. 0° 13' E., bet. secs. 15 and 16.