

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Meridian, Oregon

15616

CHAINS	
	Descend 440 ft. over NW. slope, through moderate timber and undergrowth.
19.88	Point for the S 1/16 sec. cor. of secs. 15 and 16.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">S 1/16 S 16 S 15 1975</p>
	from which
	A fir, 8 ins. diam., bears S. 22° E., 29 lks. dist., mkd. S 1/16 S15 BT.
	A fir, 8 ins. diam., bears S. 79° W., 55 lks. dist., mkd. S 1/16 S16 BT.
	Descend 70 ft. over NW. slope, leave timber, enter open field, edges bear N. and W.
26.55	South Myrtle Creek, 30 lks. wide, course S. 30° W.; asc. 165 ft. over SE. slope, through open field.
29.40	County Road No. 18, paved, 35 lks. wide, bears N. 65° E. and S. 65° W., leave open field, enter moderate timber and undergrowth, edge bears same.
39.76	The ¼ sec. cor. of secs. 15 and 16, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1961, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	<p style="text-align: center;">COUNTY SURVEYORS OFFICE T 29 S ¼ S 16 S 15 R 3 W 1961</p>
	from which the original bearing trees
	A fir, 40 ins. diam., bears N. 45° E., 15 lks. dist., with healed blaze. I rescribe this tree ¼ S15 BT.
	A fir, 28 ins. diam., bears S. 75° W., 52 lks. dist., with healed blaze. This tree was rescribed by Byron, in 1961, with ¼ S16 CS BT visible on open blaze.
	N. 0° 01' E., beginning new measurement.
	Ascend 30 ft. over SE. slope, through logged area and heavy undergrowth.
1.30	Dirt road, 20 lks. wide, bears N. 75° W. and S. 75° E.
7.85	Ravine, drains S. 35° E.; asc. 175 ft. over SE. slope.
19.95	Point for the N 1/16 sec. cor. of secs. 15 and 16.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd.

*Find OK 6/92
W. Ruppert M115-48*