

Subdivision of Section 15, T. 29 S., R. 3 W.,
Willamette Meridian, Oregon

15620

CHAINS 5.25	Ridge, bears N. 58° E. and S. 58° W.; desc. 500 ft. over NW. slope.
20.26	Point for the center S 1/16 sec. cor. of sec. 15. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd.
	C S 1/16 S 15 C 1975
	from which A cedar, 6 ins. diam., bears S. 2° W., 12 lks. dist., mkd. CS 1/16 S15 BT. A cedar, 14 ins. diam., bears N. 8½° W., 22 lks. dist., mkd. CS 1/16 S15 BT. Descend 235 ft. over NW. slope, through heavy timber and dense undergrowth.
31.60	Creek, 3 lks. wide, course S. 56° W.; asc. 180 ft. over SW. slope, through logged area.
33.05	Dirt road, 15 lks. wide, bears N. 80° E. and S. 70° W.
38.50	Spur, slopes S. 85° W.; desc. 10 ft. over NW. slope.
40.52	Point for the center ¼ sec. cor. of sec. 15, at intersection with the E. and W. center line. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T 29 S R 3 W C ¼ S 15 1975
	from which A cedar, 6 ins. diam., bears S. 64° E., 19 lks. dist., mkd. C¼ S15 BT. A cedar, 16 ins. diam., bears N. 61° W., 39 lks. dist., mkd. C¼ S15 BT. Descend 215 ft. over NW. slope.
55.75	Leave logged area, enter open field, edge bears NE. and SW.
60.33	Point for the center N 1/16 sec. cor. of sec. 15. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	C N 1/16 S 15 C 1975
	from which A fir, 18 ins. diam., bears N. 60° E., 147 lks. dist., mkd. CN 1/16 S15 BT.