

15621

Subdivision of Section 15, T. 29 S., R. 3 W.,
Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 16 ins. diam., bears S. 45° W., 87 lks. dist., mkd. CN 1/16 S15 BT.</p> <p>Descend 55 ft. over NW. slope.</p>
62.85	Leave open field, edge bears E. and W.; enter scattered timber and undergrowth.
65.85	South Myrtle Creek, 35 lks. wide, course S. 75° W.; asc. 160 ft. over SW. slope, through logged area and moderate undergrowth.
72.15	County Road No. 18, paved, 35 lks. wide, bears N. 50° E. and S. 50° W.
83.17	The ½ sec. cor. of secs. 10 and 15.
	<p>From the ½ sec. cor. of secs. 14 and 15.</p> <p>N. 84° 58' W., on the E. and W. center line of sec. 15.</p> <p>Descend 380 ft. over NW. slope, along S. edge of logged area, edge bears E. and W., through moderate undergrowth.</p>
17.70	Creek, 3 lks. wide, course S. 60° W.; leave logged area, edges bear E. and N.; asc. 15 ft. over SE. slope, through moderate timber and undergrowth.
19.18	Point for the center E 1/16 sec. cor. of sec. 15.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \quad \text{S } 15 \quad \text{C} \\ 1975 \end{array}$ </p> <p>from which</p> <p>A fir, 8 ins. diam., bears N. 19° E., 28 lks. dist., mkd. CE 1/16 S15 BT.</p> <p>A fir, 20 ins. diam., bears S. 43° W., 27 lks. dist., mkd. CE 1/16 S15 BT.</p> <p>Ascend 30 ft. over SE. slope.</p>
24.30	Spur, slopes SW.; desc. 25 ft. over broken SW. slope.
38.36	The center ½ sec. cor. of sec. 15.
	Descend 290 ft. over SW. slope, through logged area and heavy undergrowth.
48.10	Dirt road, 20 lks. wide, bears N. 60° E. and S. 60° W.
50.80	Leave logged area and enter open field, edge bears N. 60° E. and S. 60° W.
57.63	Point for the center W 1/16 sec. cor. of sec. 15.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.