

Subdivision of Section 15, T. 29 S., R. 3 W.,
Willamette Meridian, Oregon

15624

CHAINS	
11.10	Ravine, drains S. 45° E.; asc. 100 ft. over SE. slope.
14.50	Spur, slopes S. 45° E.; desc. 35 ft. over NE. slope.
17.05	Ravine, drains S. 70° E.; asc. 80 ft. over SE. slope.
19.88	Point for the NW 1/16 sec. cor. of sec. 15, at intersection with the E. and W. center line. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. NW 1/16 S 15 1975 from which A fir, 12 ins. diam., bears N. 42° E., 43 lks. dist., mkd. NW 1/16 S15 BT. A fir, 12 ins. diam., bears N. 22° W., 80 lks. dist., mkd. NW 1/16 S15 BT. Ascend 10 ft. over SE. slope.
20.10	Spur, slopes E.; desc. 25 ft. over NE. slope.
23.55	Ravine, drains S. 45° E.; asc. 95 ft. over SE. slope.
28.95	Spur, slopes S. 60° E.; desc. 65 ft. over NE. slope.
30.50	Ravine, drains S. 70° E.; asc. 180 ft. over SE. slope.
38.00	Spur, slopes N. 85° E.; desc. 55 ft. over NE. slope.
41.27	The W 1/16 sec. cor. of secs. 10 and 15. From the center N 1/16 sec. cor. of sec. 15. N. 84° 50' W., on the E. and W. center line of the NW¼ of sec. 15. Descend 45 ft. over NW. slope, through open field.
4.80	South Myrtle Creek, 35 lks. wide, course S. 25° W.; asc. 210 ft. over SE. slope.
10.90	Wire fence, bears N. 36° E. and S. 36° W., leave open field, enter logged area, edge bears same.
11.80	County Road No. 18, paved, bears N. 36° E. and S. 36° W.
19.59	The NW 1/16 sec. cor. of sec. 15. Ascend 75 ft. over SE. slope.
26.35	Spur, slopes S. 30° E.; desc. 50 ft. over SW. slope.
29.35	Ravine, drains S. 20° E.; asc. 15 ft. over SE. slope.
30.95	Spur, slopes S. 10° E.; desc. 30 ft. over SW. slope.
32.75	Ravine, drains S. 10° E.; asc. 30 ft. over SE. slope.
36.15	Spur, slopes S. 20° E.; desc. 25 ft. over SW. slope.