

Remonumentation of Certain Original Corner Points,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CRAINS

and a bearing tree mkd. by Richard L. Templin, Registered Engineer No. 3024, in 1957

A fir, 17 ins. diam., bears N. 33° E., 15½ lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 33 S R 5 W  
S 32  
¼ S 5  
T 34 S  
1974

from which a new bearing tree

A fir, 20 ins. diam., bears S. 17½° W., 34½ lks. dist., mkd. ¼ S5 BT.

Corner is located on a SE. slope, 25 lks. north of a wet ravine, drains S. 80° E.

East Boundary, T. 33 S., R. 5 W.,  
Willamette Meridian, Oregon

(Remonumenting a corner established by Edward F. Sharp,  
U. S. Deputy Surveyor, in 1894)

The cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., monumented with the original basalt stone, 24 x 16 x 14 ins., firmly set 18 ins. in the ground, mkd. with 2 notches on N. and 4 notches on S. edges, from which the original bearing trees:

A fir, 31 ins. diam., bears N. 56° E., 31 lks. dist., with healed double blaze.

A white fir, 15 ins. diam., bears S. 39° E., 32 lks. dist., with healed double blaze. (Record, S. 41° E.)

A cedar, 21 ins. diam., bears S. 12° W., 30 lks. dist., with healed double blaze.

A white fir, 20 ins. diam., bears N. 15° W., 29½ lks. dist., with healed double blaze. (Record, 31 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 33 S  
R 5 W R 4 W  
S 12 | S 7  
S 13 | S 18  
1974

from which new bearing trees

*Templin R.*

*Douglas W.*