

Remonumentation of Certain Original Corner Points,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

A yew, 6 ins. diam., bears S. 60° E., 21 lks.
dist., mkd. T33S R4W S18 BT.

A cedar, 11 ins. diam., bears N. 68° W., 59½ lks.
dist., mkd. T33S R5W S12 BT.

Deposit corner stone alongside iron post.

Original

Subdivisions, T. 33 S., R. 5 W.,
Willamette Meridian, Oregon

(Remonumenting corners established by Edward F. Sharp,
U. S. Deputy Surveyor, in 1894)

The ¼ sec. cor. of secs. 25 and 26, monumented with the
original basalt stone, 18 x 12 x 6 ins., loosely set 10
ins. in the ground, mkd. ¼ on W. face, from which the
remains of the original bearing trees:

A fir, 27 ins. diam., bears S. 17° E., 22 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 33 S R 5 W
¼
S 26 | S 25
1974

from which a new bearing tree

A fir, 16 ins. diam., bears S. 72¼° W., 36 lks.
dist., mkd. ¼ S26 BT.

Deposit corner stone alongside iron post.

The ¼ sec. cor. of secs. 23 and 24, monumented with the
original basalt stone, 24 x 18 x 10 ins., firmly set 16
ins. in the ground, mkd. ¼ on W. face, from which the
remains of the original bearing trees:

A fir, 49 ins. diam., bears S. 50° E., 54 lks.
dist., with illegible scribe marks visible on
open blaze. (Record, 56 lks.)

A sugar pine snag, 35 ins. diam., bears N. 72° W.,
83½ lks. dist., with scribe marks ¼ S BT visible
on open blaze. (Record, 89 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins.
in the ground, to solid rock, and in a mound of stone,
3 ft. base, to top, with brass cap mkd.

T 33 S R 5 W
¼
S 23 | S 24
1974

from which new bearing trees

Original